

# Accessories



**AR-TAGKMFNS50**  
Mifare Polly Sogaetek Key-chain (Read Write Thin)

Non-battery operated.

Date format: MF1  
Frequency: 13.56MHz  
Transponder Type: Passive  
Temperature: -20°C to + 60°C  
Dimension: 65(L)x25(W)x3(H)mm



**AR-TAGK73W20F**  
Mifare Key-chain (Read Write Thin)

Non-battery operated.

Date format: MF1  
Frequency: 13.56MHz  
Transponder Type: Passive  
Temperature: -20°C to + 60°C  
Dimension: 47(L)x23(W)x5(H)mm



**AR-TAGCI3W50F**  
Mifare Card (Read Write Thin)

Non-battery operated.  
Credit-card size.

Date format: MF1  
Frequency: 13.56MHz  
Transponder Type: Passive  
Temperature: -20°C to + 60°C  
Dimension: 86(L)x54(W)x0.8(H)mm



**DSA-18PFM-12 FUS**  
Power Adaptor(US)

Input voltage: 100-240VAC, 50/60Hz, 0.7A  
Output voltage: 12VDC, 1500mA  
Dimension: 73(L)x51(W)x35(H)mm



**BP-W12-2000**  
Power Adaptor

Input voltage: 100VAC, 60Hz  
Output voltage: 12VDC, 2000mA  
Dimension: 85(L)x67(W)x56(H)mm



**BP-W15-2400**  
Power Adaptor

Input voltage: 100-240VAC, 50/60Hz  
Output voltage: 12VDC, 2400mA  
Dimension: 118(L)x46(W)x34(H)mm