

Accessories



AR-TAGKMFNS50
Mifare Polly Sogaetek Key-chain (Read Write Thin)

Non-battery operated.

Date format: MF1
Frequency: 13.56MHz
Transponder Type: Passive
Temperature: -20°C to + 60°C
Dimension: 65(L)x25(W)x3(H)mm



AR-TAGK73W20F
Mifare Key-chain (Read Write Thin)

Non-battery operated.

Date format: MF1
Frequency: 13.56MHz
Transponder Type: Passive
Temperature: -20°C to + 60°C
Dimension: 47(L)x23(W)x5(H)mm



AR-TAGCI3W50F
Mifare Card (Read Write Thin)

Non-battery operated.
Credit-card size.

Date format: MF1
Frequency: 13.56MHz
Transponder Type: Passive
Temperature: -20°C to + 60°C
Dimension: 86(L)x54(W)x0.8(H)mm



DSA-18PFM-12 FUS
Power Adaptor(US)

Input voltage: 100-240VAC, 50/60Hz, 0.7A
Output voltage: 12VDC, 1500mA
Dimension: 73(L)x51(W)x35(H)mm



BP-W12-2000
Power Adaptor

Input voltage: 100VAC, 60Hz
Output voltage: 12VDC, 2000mA
Dimension: 85(L)x67(W)x56(H)mm



BP-W15-2400
Power Adaptor

Input voltage: 100-240VAC, 50/60Hz
Output voltage: 12VDC, 2400mA
Dimension: 118(L)x46(W)x34(H)mm